



RHH/RHW-2/USE-2

**Underground Service Entrance Cable, 600V
UL Standard 854 for Type USE-2 and Standard
44 for Types RHH and RHW-2**

CONDUCTOR		Insulation Thickness	Bare Conductor Diameter	Overall Cable Diameter	Approx. Cable Weight	Approx. Conductor Weight
SIZE (AWG)	NUMBER OF WIRES	mils	mils	mils	lbs/1000 ft	lbs/1000 ft
6	7	60	169	290	44	25
4	7	60	213	335	63	39
2	7	60	268	390	92	62
1	18	80	299	460	122	79
1/0	18	80	336	500	148	99
2/0	18	80	376	540	179	125
3/0	18	80	423	590	217	157
4/0	18	80	475	635	265	199
250	35	95	520	710	320	235
300	35	95	570	760	374	282
350	35	95	616	810	428	329
400	35	95	659	850	482	376
500	35	95	736	930	588	469
600	58	110	813	1035	713	563
700	58	110	877	1100	818	657
750	58	110	908	1130	870	704
900	58	110	999	1219	1030	847
1000	58	110	1060	1280	1132	939

NOTES:

- Data are approximate and subject to normal manufacturing tolerances.
- The suffix-2 indicates that these wire types can be used at a continuous 90° C operating temperature in dry and wet locations.
- RoHS Compliant