



SEU ALUMINUM

**Service Entrance Cable Type SE Style U. 600V
ASTM Standards B800, B801, and B836.
UL Standard 854**

TWO CONDUCTOR SEU WITH A BARE GROUND				
INSULATED CONDUCTOR SIZE (AWG)	BARE CONDUCTOR SIZE (AWG)	Nominal Outside Diameter	Approx. Net Weight	Approx. Conductor Weight
		in	lbs/ 1000 ft	lbs/ 1000 ft
8	8	0.432 x 0.656	184	108
6	6	0.467 x 0.726	190	129
4	6	0.511 x 0.814	229	157
4	4	0.511 x 0.814	229	157
2	4	0.566 x 0.924	288	204
2	2	0.566 x 0.924	288	204
1	1	0.617 x 1.260	343	236
1/0	2	0.654 x 1.100	395	278
1/0	1/0	0.654 x 1.100	415	298
2/0	1	0.694 x 1.180	459	329
2/0	2/0	0.701 x 1.197	507	376
4/0	2/0	0.810 x 1.395	684	524
4/0	4/0	0.849 x 1.434	761	598

NOTES:

- Data are approximate and subject to normal manufacturing tolerances.
- Cross-linked polyethylene (XLPE) insulation on the aluminum alloy conductors is rated for a maximum operating temperature of 90° C in wet and dry locations; the SE cable assembly is listed for use at 75° C.
- RoHS Compliant