



**Aluminum Underground
Distribution Cable
Triplex Type USE-2 600 V
ANSI/ICEA S-105-692, ASTM B231
UL Standard 854**

Code Word	PHASE CONDUCTOR			NEUTRAL			Approx. O.D. mils	Approx. Cable Weight lbs/1000 ft	Approx. Conductor Weight lbs/1000 ft
	SIZE (AWG)	No. of Wires	Insulation Thickness	SIZE (AWG)	No. of Wires	Insulation Thickness			
			mils			mils			
TRIPLEXED WITH TRIPLE SOLID YELLOW STRIPES NEUTRAL									
Erskine	6	7	60	6	7	60	640	133	74
Vassar	4	7	60	4	7	60	740	190	118
Stephens	2	7	60	4	7	60	840	248	164
Ramapo	2	7	60	2	7	60	870	277	187
Brenau	1/0	19	80	2	7	60	1040	384	261
Bergen	1/0	19	80	1/0	19	80	1100	437	298
Converse	2/0	19	80	1	19	80	1150	474	329
Hunter	2/0	19	80	2/0	19	80	1200	530	375
Hollins	3/0	19	80	1/0	19	80	1250	576	415
Rockland	3/0	19	80	3/0	19	80	1300	645	473
Sweetbriar	4/0	19	80	2/0	19	80	1360	702	523
Monmouth	4/0	19	80	4/0	19	80	1420	789	597
Pratt	250	37	95	3/0	19	80	1530	852	628
Wesleyan	350	37	95	4/0	19	80	1690	1111	858
Rider	500	37	95	350	37	95	2030	1596	1269

- The above data is approximate and subject to normal manufacturing tolerances.
- The suffix-2 indicates that these wire types can be used at a continuous 90o C operating temperature in dry and wet locations.
- RoHS Compliance